

## CPS2-78

### 2 way coaxial cable splitter 68 - 88 MHz

#### Beschreibung

- The CPS series of power splitters are manufactured using high quality coaxial cable and connectors.
- The CPS power splitters use quarter wave coaxial cable transformer sections to match two or more loads to one source.
- The junction points on the CPS power splitters are completely encapsulated with polyurethane resin within an aluminium tube totally preventing dust and moisture ingress.
- Former Skymasts brand product.



#### BESTELLUNG

Modell	Produkt Nr	Frequenz
2 way coaxial cable splitter	CPS2-78	66 - 88 MHz

#### SPEZIFIKATIONEN

Elektrisch DE	
Modell	CPS2-78
Frequenz	66 - 88 MHz
Max. Eingangsleistung	500 W
Einfügedämpfung	-3.2 dB
Impedanz	50 $\Omega$
VSWR	< 1.3:1
Mechanisch DE	
Anschlussstyp	N(f) an 1m RG213 / U Kabel
Output-Anschlüsse	N(m) (auf Viertelwellenlängenkabel)
Körpermaterial	Aluminium tube 38.1 mm
Isolator	Polyurethanharz-Verkapselung
Anzahl der ausgänge	2
Umwelt	
IP Schutzklasse	IP68

